


Index No. E5

CASS COUNTY LAND CORNER RECORD

T. 141 R. 30 M. 5TH Coordinates: X _____ Y _____
NE 7 Corner common to sections 5, 6, 7, 8



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Tree	Distance
<u>MAPLE</u>	<u>ELM</u>	<u>POPLAR</u>	<u>PINE</u>
<u>8"</u>	<u>7"</u>	<u>4"</u>	<u>7"</u>
<u>N72W</u>	<u>N11E</u>	<u>S16 1/2 W</u>	<u>S45E</u>
<u>14 LKS</u>	<u>61 LKS</u>	<u>64 LKS</u>	<u>80 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By ROAD SURVEY
Location filed COUNTY BOOK D' P. 105
Monument IRON MONUMENT
1941, JOHN CURD, BOOK D' P. 257 1 1/2" SOLID IRON

Evidence of Subsequent Corner Restoration

Year of search 1917 By GLO
FIND OLD WOOD STAKE AND NW 1/4 SW B.T. STUMPS.
SET 2X36" 1/4" W/BRASS CAP 7141N R30W
56 | 55
57 | 58
1917

Bearing Trees, Reference Objects

Species	Bearing	Tree	Distance
<u>W. BIRCH</u>	<u>W. BIRCH</u>	<u>R. OAK</u>	<u>W. OAK</u>
<u>6"</u>	<u>5"</u>	<u>6"</u>	<u>6"</u>
<u>N55-20E</u>	<u>S62-20E</u>	<u>S38-55W</u>	<u>N29-40W</u>
<u>183.50'</u>	<u>202.50'</u>	<u>116.30'</u>	<u>169.90'</u>

Bearing Trees, Reference Objects

Species	Bearing	Tree	Distance
<u>OAK</u>	<u>OAK</u>	<u>MOUND OF STONE</u>	
<u>12"</u>	<u>12"</u>	<u>2' BASE</u>	
<u>S89W</u>	<u>N88 3/4 W</u>	<u>1 1/2' HIGH</u>	
<u>186 LKS</u>	<u>143 LKS</u>	<u>W. OF COR.</u>	

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____