


T. 141 R. 31 M. 574 Coordinates: X NE 5 Y 4, 3 AND 32, 33 - 142-31
Corner common to sections



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Species	Bearing	Trees	Distance
<u>POPULAR</u>	<u>POPULAR</u>	<u>POPULAR</u>	<u>POPULAR</u>
<u>3"</u>	<u>3"</u>	<u>4"</u>	<u>3"</u>
<u>N61E</u>	<u>N25W</u>	<u>S27W</u>	<u>S47E</u>
<u>13LKS</u>	<u>13LKS</u>	<u>31LKS</u>	<u>10LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1925 By JOHN GREENE

Location filed COUNTY RESURVEY "E-51"

Monument EVIDENCE OF OLD SURVEYS

1919-E.B. HORST, COUNTY RESURVEY PLAT "E-62" T.M.

1925-JOHN GREENE, ✓ ✓ ✓ ✓

1917-E.B. HORST - microfilm - roll 115 BK 86 P. 67-68

Set T.M. Proportionately

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 1916 By F.F. WILSON

COUNTY BOOK "C" P. 121 SET WOOD POST & TACK

FOR TRUE CORNER FROM RAILROAD INFO.

1919, E.B. HORST, BOOK "C" P. 499 Fwd T.M.

also on microfilm - roll 115 BK 86 P. 75-87

1916 - also on microfilm - roll 115 BK 86 P. 45

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>POPULAR</u>	<u>POPULAR</u>	<u>POPULAR</u>	<u>POPULAR</u>
<u>4"</u>	<u>3"</u>	<u>4"</u>	<u>5"</u>
<u>S39-30E</u>	<u>S87-30W</u>	<u>N42E</u>	<u>N20W</u>
<u>17'</u>	<u>35.4'</u>	<u>41'</u>	<u>38.3'</u>
<u>1916 ties</u>			

Subsequent Corner Restoration

Year surveyed 5/01 By Landecker

Location filed Cass Co. Recorder

Monument Found 1962 Brass cap, 100'±

SE of F.S. Rd. #2822 and witnessed

as follows:

3" W. Oak, North, 12.98'

7" W. Oak, S36°E, 12.63'

4" Ironwood, S16°W, 22.49'

Sign Post, West, 1.8'

A Cert. of Loc. was filed

Lat. 47°04'08.5098"

Long. 94°37'08.1658"

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - PETE MEYER - 1962

Found 2"x48" iron monument. Set 2"x5'

galvanized wrought iron pipe filled with

concrete and capped with 3" stamped

bronze tablet. Ties: 6" Elm NSW 25.8';

7" Oak N24E 56.3'; 3x2 1/2 x 1' rock S62 1/2 E

6.0'.

Feb 2001 T. Freeman 21367

Cert. of svy shows Mon Found

Sept. 1917, Twp rd order shows no survey.