


Index No. N1

CASS COUNTY LAND CORNER RECORD



141 R. 31 M. 5TH Coordinates: X _____ Y _____
NW 19 Corner common to sections 18, 19

EXISTING SURVEYS

Original Government Survey
 Year surveyed 1871
 Original monument POST

Species	B. PINE	B. PINE	B. PINE	B. PINE
Diameter	<u>14"</u>	<u>8"</u>	<u>8"</u>	<u>10"</u>
Bearing	<u>N38W</u>	<u>N70E</u>	<u>S70E</u>	<u>S65W</u>
Distance	<u>32LKS</u>	<u>62LKS</u>	<u>36LKS</u>	<u>67LKS</u>

Original Evidence Found
 Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found
 Species _____
 Diameter _____
 Bearing _____
 Distance _____

O = Corner

Subsequent Corner Restoration
 Year surveyed 1927 By JOHN GREENE
 Location filed COUNTY RESURVEY PLAT "E-52"
 Monument IRON MONUMENT

Evidence of Subsequent Corner Restoration
 Year of search 1929 By Thos. H. Y. Dept.
R/W map in Recorder's office - Walker to
AKelley
1 1/2" iron pipe

Bearing Trees, Reference Objects

Species _____
 Diameter _____
 Bearing _____
 Distance _____

Bearing Trees, Reference Objects

Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - HAROLD CURD - 1958
Set 234 x 60" capped monument filled with
concrete; Ties: 16" J. Pine S56°17'E 55.60';
13" J. Pine S89°E 50.20'; 8" J. Pine N1°57'W
58.9'.

Remonumentation certificate prepared _____ By _____
 Filed at _____ Date _____