Index No. R 17

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____

NE 27 Corner common to sections 22, 23, 26, 27



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	POPLAR	POPLAR	OAK	Y. PINE
Diameter	10"	10"	6"	18"
Bearing	N77E	N55W	S40W	S55E
Distance	10 LKS	28 LKS	38 LKS	12 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1922 By E.B. HORST

Location filed COUNTY RESURVEY PLAT "E-53"

Monument 2x48" IRON MONUMENT

1920, E.B. HORST, BOOK "C" P.460 FND NE & NW BITS - SET 2x48" I.M also stump of SE B.T.

Bearing Trees, Reference Objects

Species	W. OAK	W. OAK		
Diameter	10"	12"		
Bearing	S54E	N86-30W		
Distance	60'	24.5'		

Evidence of Subsequent Corner Restoration

Year of search 1952 By HAROLD CURO

COUNTY BOOK "D" P.400 FND 2"x48" I.M w/CAP

Bearing Trees, Reference Objects

W. PINE	W. PINE	POPLAR	POPLAR
16"	6"	8"	8"
N46-42E	N38W	S15-35W	S54-40E
56.10'	53.50'	23.25'	13.80'

R-17

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - HAROLD CURO - 1959

Certificate - Walt Curo - 1987

Doc # 302143

Fnd 2 3/4 x 60" I.P. w/cap as per 1959 Certificate

12" Red oak N 46 E 18.71'

8" Red oak S39W 14.50'

10" Red oak N75W 21.3'

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____