


Index No. R 20-21

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 574 Coordinates: X <sup>Long</sup> 94°33'22.1860" Y <sup>Lat</sup> 47°00'47.6666"  
MC# 18 Corner common to sections 23, 26



EXISTING SURVEYS

Original Government Survey  
Year surveyed 1873  
Original monument Post

Original Evidence Found  
Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees  
Species J. Pine Poplar  
Diameter 14" 8"  
Bearing N40W S21W  
Distance 14LKS 10 RKS

Original Bearing Trees Found  
Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration  
Year surveyed 1922 By E. B. Horst  
Location filed COUNTY RESURVEY PLAT "E-53"  
Monument 24 1/8" IRON MONUMENT  
1920, E. B. HORST, BOOK "C" P. 460 END CORNER.  
also on microfilm - roll 115 BK 80 P. 98

Evidence of Subsequent Corner Restoration  
Year of search 1961 By McDonald USFS  
Found 2" IP and J. Pine windfall.

Bearing Trees, Reference Objects  
Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Bearing Trees, Reference Objects  
J. Pine  
N42°W  
9.3'

R-20, 21 Subsequent Corner Restoration  
Year surveyed 1980 By USFS  
Location filed Cass Lake office  
Monument Found 2" IP, placed rock mound around monument.

Sign Post West, 16.55'  
16" W. Pine S9°W, 17.75'

7/2001 LEA found 2" IP, up 2.6', placed 3" Alum cap on monument. Found 1980 witnesses good, add the following:  
6" Oak N86°W, 35.04'

Evidence of Subsequent Corner Restoration Found  
Year of search \_\_\_\_\_ By \_\_\_\_\_

Re monumentation certificate prepared 11/1/01  
Filed at Cass Co. Recorder #442511

By Freeman  
Date \_\_\_\_\_