


T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 34 Corner common to sections 26, 27, 34, 35



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Species	Bearing	Trees	
<u>PINE</u>	<u>MAPLE</u>	<u>LYNN</u>	<u>BIRCH</u>
Diameter <u>8"</u>	<u>8"</u>	<u>5"</u>	<u>4"</u>
Bearing <u>N70W</u>	<u>N60E</u>	<u>S31E</u>	<u>S42W</u>
Distance <u>18LKS</u>	<u>5LKS</u>	<u>11LKS</u>	<u>24LKS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species _____

Diameter _____

Bearing _____

Distance _____

○ = Corner

Subsequent Corner Restoration

Year surveyed 1922 By E.B. HORST

Location filed COUNTY RESURVEY PLAT 'E-53'

Monument 2448" IRON MONUMENT
1928, JOHN GREENE, COUNTY RESURVEY PLAT 'E-55' I.M.
1921, E.B. HORST, BOOK 'C' P. 468 SET 2x48" I.M.

Evidence of Subsequent Corner Restoration

Year of search 1987 By Walt Curo

Corner Certificate - Doc # 302148
Find 2 7/4" 1 1/2" w/ cap as per 1959 Certificate and
1960 USFS information

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>12" Burr oak</u>	<u>20"</u>	<u>S 24 E</u>	<u>51.90'</u>
<u>N. Pine</u>	<u>10"</u>	<u>S 25 W</u>	<u>83.19'</u>
<u>Red oak</u>	<u>18"</u>	<u>N 43 W</u>	<u>49.40'</u>
			<u>76.46'</u>
			<u>1980 BT</u>
			<u>1959 BT</u>
			<u>1980 BT</u>

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - HAROLD CURO - 1959

Certificate - Walt Curo - 1987