


Index No. V5

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 31 Corner common to sections 29, 30, 31, 32



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
 Original monument POST

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Species	Bearing	Trees	
<u>POPULAR</u>	<u>POPULAR</u>	<u>BIRCH</u>	<u>BIRCH</u>
Diameter <u>6"</u>	<u>8"</u>	<u>6"</u>	<u>4"</u>
Bearing <u>S9W</u>	<u>N12W</u>	<u>S66E</u>	<u>N51E</u>
Distance <u>6LKS</u>	<u>9LKS</u>	<u>4LKS</u>	<u>10LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

O = Corner

Subsequent Corner Restoration

Year surveyed 1921 By E. G. HORST
 Location filed COUNTY RESURVEY PLAT "E-54, E-55"
 Monument IRON MONUMENT
1921, E. G. HORST, BOOK "C" P. 445 FRO WOOD POST SET FROM
NW, SW & SE BITS STUMPS. P. 456 SET 2x40" I.M

Evidence of Subsequent Corner Restoration

Year of search 1984 By Tony Kerick
Corner Certificate
Found 3" brass cap set in 1962 by Pete Meyer

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

W. Pine	R. oak	Cedar post	N. P. ne
<u>22" Now 28"</u>	<u>12"</u>	<u>4x4</u>	<u>14" Now 20"</u>
<u>N40 1/2 W</u>	<u>N62 E</u>	<u>S64 1/2 E</u>	<u>S42 1/2 W</u>
<u>59.30'</u>	<u>7.75'</u>	<u>4.9'</u>	<u>43.30'</u>
<u>1962 tie</u>			<u>1962 tie</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - PETE MEYER - 1962
Certificate - Tony Kerick - 1984
Doc. # 280490

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____