


Index No. Z 22-23

CASS COUNTY LAND CORNER RECORD

T. 141 R. 31 M. 5TH Coordinates: X _____ Y _____
MC# 1 Corner common to sections 36



EXISTING SURVEYS

Original Government Survey

Year surveyed 1863
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>y. Pine</u>	<u>y. Pine</u>	
<u>16</u>	<u>15</u>	
<u>N20E</u>	<u>S21E</u>	
<u>14 lks</u>	<u>39 lks</u>	

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1915 By N.O. Gorman
Location filed microfilm - roll 105 BK 63 P. 10-11
Monument End SE tree and stump of NE B.T.
set 80 d spike
on P. 52 - set 2x48" I.M.

Evidence of Subsequent Corner Restoration

Year of search 1978 By W. Curo
Found iron monument in place.
Plat of Hillaway East.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

2-22, 23

Subsequent Corner Restoration

Year surveyed 7/03 By CCSO
Location filed Top file
Monument Found 2" ODIP w/plumber cap,
up 1.5', on top of bank, 6'± from
lake. Witnessed as follows:

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

- 17" N. Pine snag S20°E, 26.2' (CLO)
- 11" N. Pine S42°E, 30.79' *
- 11" N. Pine N33°E, 15.04' *
- * distance to double head nail

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____