


Index No. N 23

CASS COUNTY LAND CORNER RECORD

T. 142 R. 26 M. 5TH Coordinates: X _____ Y _____
N 1/4 24 Corner common to sections 13, 24



EXISTING SURVEYS

Original Government Survey

Year surveyed 1872
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees	
Species	<u>W. PINE</u> <u>N. PINE</u>
Diameter	<u>40"</u> <u>24"</u>
Bearing	<u>N 43 W</u> <u>S 34 E</u>
Distance	<u>20 LKS</u> <u>50 LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration

Year of search 1997, July By Laverne Leuelling
Monumented Qtr. Corner position established
on line between NE & NW corners of Sec. 24
& at record distance from the calc. NE corner
of Sec. 24.
Cert. Filed: Dec. 8, 1997; Doc #395066

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>Ash</u>	<u>Ash</u>	<u>Ash</u>	<u>St. Signpost</u>
<u>0.137m</u>	<u>0.102m</u>	<u>0.152m</u>	
<u>N 85 W</u>	<u>S 28 W</u>	<u>N 18 E</u>	<u>N</u>
<u>7.060m</u>	<u>6.626m</u>	<u>15.348m</u>	<u>0.690m</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____