


T. 142 R. 27 M. 5TH Coordinates: X _____ Y _____
NE 28 Corner common to sections 21, 22, 27, 28



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

| Species | Bearing Trees | | | |
|----------|----------------|----------------|---------------|---------------|
| | <u>FIR</u> | <u>POPULAR</u> | <u>FIR</u> | <u>FIR</u> |
| Diameter | <u>6"</u> | <u>14"</u> | <u>10"</u> | <u>8"</u> |
| Bearing | <u>S32W</u> | <u>S78E</u> | <u>N71E</u> | <u>N15W</u> |
| Distance | <u>10 LKS.</u> | <u>15 LKS</u> | <u>14 LKS</u> | <u>25 LKS</u> |

Original Bearing Trees Found

| Species | Diameter | Bearing | Distance |
|---------|----------|---------|----------|
| | | | |
| | | | |
| | | | |

Subsequent Corner Restoration

Year surveyed 1981 By G.H. STEVENSON
Location filed PLAT OF SURVEY E-74"
Monument FOUND VS GLO BRASS CAPPED MONUMENT LEFT IN PLACE

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLO
FND DECAYED WOOD STAKE AND ORIG B.TS: 7142N R27W
12" CEDAR STUMP S32W 10 LKS, DECAYED POPULAR 521 | 522
STUMP S78E 15 LKS, 12" CEDAR STUMP N15W 528 | 527
25 LKS. SET 2X36" I.P.W/BRASS CAP, 1919
NORTH AND ALONGSIDE OLD STAKE

Bearing Trees, Reference Objects

| Species | Bearing Trees, Reference Objects | | |
|----------|----------------------------------|---------------|---------------|
| | <u>ASH</u> | <u>W. OAK</u> | <u>ASH</u> |
| Diameter | <u>6"</u> | <u>6"</u> | <u>6"</u> |
| Bearing | <u>N60W</u> | <u>N65E</u> | <u>S52E</u> |
| Distance | <u>14.37'</u> | <u>33.52'</u> | <u>15.57'</u> |

Bearing Trees, Reference Objects

| Species | Bearing Trees, Reference Objects | | | |
|----------|----------------------------------|------------------|------------------|---------------|
| | <u>SPRUCE</u> | <u>ASH</u> | <u>ASH</u> | <u>ASH</u> |
| Diameter | <u>14"</u> | <u>12"</u> | <u>12"</u> | <u>6"</u> |
| Bearing | <u>N25 1/2 E</u> | <u>S36 1/2 E</u> | <u>S63 1/2 W</u> | <u>N28W</u> |
| Distance | <u>89 LKS</u> | <u>84 LKS</u> | <u>17 LKS</u> | <u>52 LKS</u> |

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
GARY STEVENSON - CERTIFICATE - 1981
Doc. # 260595
Found GLO monument in good condition.
6" Ash N60W 14.37'; 6" W. Oak N65E 33.52';
6" Ash S52E 15.57'.