Index No. A 13

CASS COUNTY LAND CORNER RECORD

T. 142 R. 28 M. 5TH Coordinates: X _____ Y _____

NE 4 Corner common to sections 3, 4 AND 33, 34-143-28



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Bearing Trees

Species	OAK	SUGAR MAPLE	SUGAR MAPLE	LIND
Diameter	24"	10"	8"	15"
Bearing	N74E	S60E	S33W	N32W
Distance	104 LKS	104 LKS	28 LKS	41 LKS

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1928 By GLO

Location filed SEC. OF STATE

Monument FND SQUARED STAKE - SET 2X36" 1/2" W/BRASS CAP

T143N R28W

533 | 534

54 | 53

T142 N R28

Bearing Trees, Reference Objects

Species	W. OAK	MAPLE	BASSWOOD	
Diameter	14"	12"	10"	
Bearing	N36E	S81E	N47W	
Distance	86 LKS	154 LKS	123 LKS	

Evidence of Subsequent Corner Restoration

Year of search DEC. 1923 By _____

Third order shows no survey

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CERTIFICATE - Gary Stevenson - 1982

Doc. #264927

Found GLO monument in good condition. 8" W. Oak S39W 69.20'; 7" W. Oak S52E 96.50'; 20" Maple N36E 56.8' (1919 BT); 5" W. Oak N37E 45.20'; 10" W. Oak N6E 23.60'.

Corner GPS CCSO ● 12/4/02

CCSO 12/4/02 Fd GLO brass cap, 18'± N. of ℄

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____