Index No. F-22

CASS COUNTY LAND CORNER RECORD

T. 142 R. 31 M. 5th Coordinates: X _____ Y _____

NW 1/16 Corner common to sections 12



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1918

Original monument 1"x36" Bor. Cap

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees				
Species	Oak	Poplar		
Diameter	4	8		
Bearing	N88E	N44W		
Distance	36 lks	26 lks		

Original Bearing Trees Found				
Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1984 By T. Freeman - USFS

Location filed USFS - C. Krause, G. Brauma, J. Allison

Monument USFS determined proportionate dist - Brass cap was torn out & bent badly. Set 9" piece of 1" I.P. w/brass cap in drilled hole in large rock. punch hole on brass cap for true location

Bearing Trees, Reference Objects				
Species	N. Pine	N. Pine	N. Pine	Steel Sign
Diameter	18"	18"	18"	Post
Bearing	S80°W	N40°W	S60°E	west
Distance	67.10'	56.43'	54.47'	8.2'

blazed, scribed, red rings and B.T. tags

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____