


Index No. V15

CASS COUNTY LAND CORNER RECORD

T. 142 R. 31 M. 5TH Coordinates: X _____ Y _____
N1/4 34 Corner common to sections 27, 34



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Bearing Trees

Species	<u>Y. Pine</u>	<u>W. Pine</u>	_____	_____
Diameter	<u>14</u>	<u>14</u>	_____	_____
Bearing	<u>N30E</u>	<u>S43W</u>	_____	_____
Distance	<u>12 lks</u>	<u>25 lks</u>	_____	_____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1921 By GLO
 Location filed _____
 Monument Fd. 2 1/2" gal. iron pipe - north and
along side set 1" x 36" Br. Cap. Orig. B's:
18" Pine stump N30E 12 lks
24" Pine stump S43W 25 lks

Evidence of Subsequent Corner Restoration

Year of search 1929 By Minn Hwt Dept.
R/W map in Recorder's Office - Walker to Akeley
iron pipe & cap in place
1915 - P.M. SCOTT - chain to iron corner from
N1/4 corner 3-141-31

Bearing Trees, Reference Objects

Species	<u>N. Pine</u>	<u>N. Pine</u>	_____	_____
Diameter	<u>8</u>	<u>8</u>	_____	_____
Bearing	<u>S57E</u>	<u>N91W</u>	_____	_____
Distance	<u>52 lks</u>	<u>54 lks</u>	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1914 By Gorman
 Location filed micr of. l.m. - roll 1115 BK92 P. 28
 Monument Set iron corner

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

March 2005 T Freeman #21367
Cert. of survey shows monument found

Re monumentation certificate prepared _____ By _____
 Filed at _____ Date _____