

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Page _____ of _____

Corner common to sections _____

Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed _____ By _____

Year of search _____ By _____

Location filed: _____

Location filed: _____

Monument: _____

Monument: _____


Certificate of Location of Government Corner filed in Cass County

By _____

Recorders Office as Document _____

Date _____

T. 143 R. 26 M. 5TH Coordinates: X _____ Y _____
NE 32 Corner common to sections 28, 29, 32, 33



EXISTING SURVEYS

Original Government Survey

Year surveyed 1872
Original monument POST

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Tree	Distance
<u>FIR</u>	<u>Birch</u>	<u>White</u>	<u>Birch</u>
<u>6"</u>	<u>5"</u>	<u>26"</u>	<u>7"</u>
<u>N18E</u>	<u>N51W</u>	<u>S50W</u>	<u>S44E</u>
<u>204s</u>	<u>154s</u>	<u>204s</u>	<u>404s</u>

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1916 By JAMES FLYNN
 Location filed COUNTY BOOK "C" P. 160
 Monument END OLD CORNER B. 133 6" FIR N18E 204S, 5" BIRCH N51E 152KS, 26" W PINE S50W 204KS, 7" BIRCH S44E 404KS
1918, BOOK "C" P. 151 END IRON ALREADY ESTABLISHED
JAMES FLYNN IRON IS 2 1/2" x 30" W/ BR. CAP
 Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>BASSWOOD</u>	<u>14"</u>	<u>N11-15E</u>	<u>64.5'</u>
<u>BL. OAK</u>	<u>14"</u>	<u>N45-30W</u>	<u>35.5'</u>

Evidence of Subsequent Corner Restoration

Year of search 1918 By JAMES FLYNN
COUNTY RESURVEY "E-3" 2 1/2" x 30" IRON
1918, C.B. HORST, BOOK "C" P. 163 START AT COR. RUN NORTH
1969 - Co. Hwy Dept - Co. Rd. # 65
found corner monument
 Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed 1916 By HORST
 Location filed Micro Film - roll 105 BR 68 P. 28
 Monument End Birch bearing tree plainly marked set I. M.
Balsam 8" N36E 27.8'
oak 12" N44W 35.2'
oak 7" S73W 14.5'
Balsam 6" S10E 30.0'

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - BILL OKERMAN - 1968
CERT. WM. OSUFSEN 1990
Doc. # 319630

1990 By WM OSUFSEN
End 6" x 60" CONC. CYLINDER w/ BR. CAP

STEEL SIGN POSTS 2.9 EAST AND 2.8 SOUTH

Species	Diameter	Bearing	Distance
<u>RED OAK</u>	<u>12"</u>	<u>N68W</u>	<u>138.71</u>
<u>BIRCH</u>	<u>3"</u>	<u>N24E</u>	<u>84.18</u>
<u>BIRCH</u>	<u>4"</u>	<u>S80E</u>	<u>87.26</u>
<u>RED OAK</u>	<u>14"</u>	<u>S12W</u>	<u>22.86</u>

Remonumentation certificate prepared _____
Filed at _____

By _____
Date _____