


T. 143 R. 27 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E114 35 Corner common to sections 35, 36



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>Cedar</u>	<u>Cedar</u>	_____
Diameter	<u>6"</u>	<u>6"</u>	_____
Bearing	<u>EAST</u>	<u>S66W</u>	_____
Distance	<u>10 LKS</u>	<u>12 LKS</u>	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1915 By JOHN CURD  
Location filed COUNTY BOOK B P. 455-462  
Monument FIND OLD GOVT BIT: 6" CEDAR EAST  
10 LKS SET 4X4X36" CEDAR POST

Evidence of Subsequent Corner Restoration

Year of search 1998 By NLSEM RLS #16089  
Set a 1/2" x 6' aluminum rod w/ alum. cap

- also on microfilm - roll 115 BK 79 P. 16

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

<u>Ash</u>	<u>Ash</u>	<u>Ash</u>	<u>Steel</u>
<u>5"</u>	<u>5"</u>	<u>7"</u>	<u>Sqn Post</u>
<u>S40°W</u>	<u>N4°E</u>	<u>S34°E</u>	<u>S2°W</u>
<u>8.46'</u>	<u>24.00'</u>	<u>41.08'</u>	<u>1.71'</u>

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_