


T. 143 R. 28 M. 5TH Coordinates: X _____ Y _____
E14 24 Corner common to sections 24 AND 19-143-27



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument POST

Bearing Trees

Species	<u>Birch</u>	<u>Birch</u>	_____
Diameter	<u>10"</u>	<u>6"</u>	_____
Bearing	<u>S40E</u>	<u>S50E</u>	_____
Distance	<u>9LKS</u>	<u>9LKS</u>	_____

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1920 By E. B. HORST

Location filed COUNTY RESURVEY 'E-7'

Monument 1920, BEN CLARK, BOOK 'C' P. 394 END POINT OF CEDAR POST P. 395 SET POST PROPORTIONALLY, P. 396 SET 3x30" IRON POST W/CAP

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 1986 By Walter Curo

Set 2"x60" galvanized iron pipe with brass cap up 18"

Bearing Trees, Reference Objects

Maple	Aspen	Elm
6"	6"	6"
N60W	N18W	N50E
88.00'	20.90'	35.64'

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

1986 Certificate - Walter Curo Doc # 291482

1998 - NLS&M DLS #16089 - Set 2"x24" steel pipe w/brass cap (1986 monument had been removed) Found 1986 witnesses and added the following:

6" Maple, N43°E, 40.56'

Steel Post, N2°E, 10.05'