


T. 143 R. 30 M. 5th Coordinates: X _____ Y _____

SMC on Corner common to sections 12

E-W 1/4 line



EXISTING SURVEYS

Original Government Survey

Year surveyed 1924
 Original monument 1x36" 1/2" w brass
Cap

SMC
C S / C
12
1924

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Bearing Trees
 Species Poplar Mound of Stone
 Diameter 8" 2"
 Bearing S58-45W 1 1/2' High
 Distance 115 LKS W. of Cor.

Original Bearing Trees Found

Species _____
 Diameter _____
 Bearing _____
 Distance _____

Subsequent Corner Restoration

Year surveyed 1983 By Walt Curo
 Location filed Corner Certificate
 Monument End brass cap monument and mound of
stone W. of corner.

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species Maple Maple Basswood
 Diameter 6" 6" 10"
 Bearing N12W S10W S65W
 Distance 25.90' 31.39' 18.38'

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Certificate - Walt Curo - filed by USFS 1984
Doc. # 2791602 dated 1983

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____