


Index No. J 11

CASS COUNTY LAND CORNER RECORD

T. 143 R. 31 M. 574 Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 14 16 Corner common to sections 9, 16



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing	Trees
<u>N. Pine</u>	<u>N. Pine</u>	
Diameter <u>24"</u>	<u>20"</u>	
Bearing <u>S37W</u>	<u>N6E</u>	
Distance <u>28 LKS</u>	<u>53 LKS</u>	

Species	Bearing	Trees
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

Subsequent Corner Restoration

Year surveyed 1957 By H. CURD  
Location filed COUNTY BOOK D 1926  
Monument FWD J.M.

Evidence of Subsequent Corner Restoration

Year of search 1919 By GLO  
Ed 2 1/2" Galv. lnl. and Stumps of both pits - set  
1 x 36" lnl. willow cup 1 1/4 59  
1919 516

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
Diameter _____	_____	_____
Bearing _____	_____	_____
Distance _____	_____	_____

Bearing Trees, Reference Objects

Species	Bearing	Distance
<u>w. Birch</u>	<u>w. Pine stump</u>	
<u>3"</u>	<u>28"</u>	
<u>S 37 1/2 W</u>	<u>N 55 1/2 W</u>	
<u>77 LKS</u>	<u>105 LKS</u>	

Subsequent Corner Restoration

Year surveyed July 2004 By B. Carnell Sr. # 43415  
Location filed \_\_\_\_\_  
Monument Cent. of Sec. Shows mon. found

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_