Index No. J 25

CASS COUNTY LAND CORNER RECORD

T. 144 R. 28 M. 5TH Coordinates: X _____ Y _____

NE 13 Corner common to sections R 13 AND 7, 18-144-27



O = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	Tam	Tam	Tam	Tam
Diameter	3"	3"	4"	4"
Bearing	S10W	S20E	N30W	N15E
Distance	14 LKS	17 LKS	12 LKS	20 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1937 By GLO

Location filed Sec. of State

Monument Set Concrete mon - 2' long 6" Dia. w/brass cap

T144N
R28W R27W
S12 | S7
S13 | S18
1937

Evidence of Subsequent Corner Restoration

Year of search 1994 11-15 By Terry Freeman

Found Concrete monument leaning in approx. 3' of water. Removed monument. 11-16-94 placed 2" x 20" iron pipe w/brass cap up 15" over 8' steel sign post. 3-16-95 Cert. Filed by Terry Freeman, RLS 21367. Doc. #365387

Bearing Trees, Reference Objects

Species	Poplar			
Diameter	9"			
Bearing	S30-40E			
Distance	453 LKS			

Bearing Trees, Reference Objects

Steel Sign Post	Steel Sign Post	Steel Sign Post	Steel Sign Post
8'	8'	8'	8'
N18E	N84E	S	E
47.70	106.00	2.30	2.35

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____