


Index No. A 17

CASS COUNTY LAND CORNER RECORD

T. 144 R. 29 M. 5TH Coordinates: X _____ Y _____
NE 3 Corner common to sections 2, 3



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument C.C. Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

Species	Bearing	Trees
<u>N. Pine</u>	<u>18"</u>	<u>N. Pine</u>
<u>18"</u>	<u>545E</u>	<u>16"</u>
<u>545E</u>	<u>1304S</u>	<u>585W</u>
<u>1304S</u>		<u>354S</u>

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1926 By GLO
Location filed Sec. of state
Monument Find SW BIT - now 36" and stump hole
of SE BIT, set 1x36" 1/2" w/brass cap T144NR29W
AP
53/52

Evidence of Subsequent Corner Restoration

Year of search 1926 By GLO
set C.C. 2x36" 1/2" w/brass cap from
orig BIT (Below) T145N R29W
535
53/52
T144N R29W
CC

Bearing Trees, Reference Objects 1926

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects 1926

N. Pine w. Oak
36" 4"
551W 564E
464K 234Ks
Remark "CC T144NR29W 530'" mark - CG 52 BIT

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - PATE MEYER - 1963 - ANGLE POINT
S 1/2 E 17.6'
Found GLO monument in good condition
25" W. Pine 564E 82.6'

Remonumentation certificate prepared _____ By _____
Filed at _____ Date _____