


T. 144 R. 29 M. 574 Coordinates: X _____ Y _____
N4413 Corner common to sections 12, 13



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873
Original monument Post

Species	Bearing	Distance	Trees
<u>Tam</u>	<u>19m</u>		
<u>8"</u>	<u>8"</u>		
<u>N45E</u>	<u>S62E</u>		
<u>14 LKS</u>	<u>15 LKS</u>		

Original Evidence Found

Year of search _____ By _____
Monument found _____

Original Bearing Trees Found

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1926 By GLD
Location filed Sec. of State
Monument Find wood stake - orig. bits: Dead 10" Tam
N64-45W 15 LKS, Dead 8" Tam N63-15E 14 LKS Spt 1x36
1. P. w/ brass cap. NOTE: Deaxms on orig 1/4 512
P.T.S. do not check - but distances do. 513
1926

Bearing Trees, Reference Objects

Species All trees in area are dead
Diameter _____
Bearing _____
Distance _____

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
CERTIFICATE - PETE MEYER - 1961

1982 Certificate - Gary Stevenson
Doc. # 264972
Found 2" iron pipe with marked 3"
brass cap.
20" N. Pine S48W 80.1' (1958 BT);
20" N. Pine S26E 82.5' (1958 BT);
8" W. Oak S47E 49.2';
9" J. Pine N61 1/2 E 166.9' (1958 BT);
10" J. Stump N54E 66.0' (1874 BT)