Index No. R 9

CASS COUNTY LAND CORNER RECORD

T. 144 R. 29 M. 5TH Coordinates: X _____ Y _____

NE 29 Corner common to sections 20, 21, 28, 29

29

○ = Corner



EXISTING SURVEYS

Original Government Survey

Year surveyed 1873

Original monument Post

Original Evidence Found

Year of search _____ By _____

Monument found _____

Bearing Trees

Species	Birch	Elm	Maple	Basswood
Diameter	16"	12"	6"	6"
Bearing	S15W	S23E	N26W	N10W
Distance	54 LKS	58 LKS	17 LKS	37 LKS

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1906 By John Curo

Location filed County Survey Record Book "A" P232-233

Monument Set oak stake from old Govt Bits: 16" Fir S15W 35.6', 12" Elm S23E 38.3', 6" Maple N26W 11.2', 6" Basswood N10W 24.4'.

Bearing Trees, Reference Objects

Species				
Diameter				
Bearing				
Distance				

Evidence of Subsequent Corner Restoration

Year of search 1923 By Horace Dunaway

Book "D" P127 Fnd Corner

1926, GLO Fnd Ash Stake SW Bit and Stump of SE Bit. Set 2x36" lip w/brass cap T144N R29W

S20 | S21
S29 | S28
1926

Bearing Trees, Reference Objects

Maple	W. Pine			
8"	8"			
S20E	N82-30W			
70 LKS	89 LKS			

1926 GLO TIES

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificate - Pete Meyer - 1963

Found GLO monument in good condition

13" Maple S20E 46.2';

23" W. Pine S25W 62.2';

18" W. Pine N83W 58.74'

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____