


T. 144 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

E 1/4 9 Corner common to sections 9, 10



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875

Original monument Post

Original Evidence Found

Year of search 1930 by Craig

Monument found \_\_\_\_\_

Minn. Hist. Society, notes 107

Bearing Trees

Species	<u>Yellow Birch</u>	<u>Yellow Birch</u>	_____
Diameter	<u>6"</u>	<u>4"</u>	_____
Bearing	<u>N 15° W</u>	<u>S 44° W</u>	_____
Distance	<u>30 links</u>	<u>14 links</u>	_____

Original Bearing Trees Found

Species	<u>Rotted Birch</u>	<u>Birch</u>	_____
Diameter	<u>Stump</u>	<u>Falls in</u>	_____
Bearing	<u>N 15° W</u>	<u>old R/R</u>	_____
Distance	<u>30 links</u>	<u>grade</u>	_____

Subsequent Corner Restoration

Year surveyed 6/1930 By H.D. Craig, US Surveyor

Location filed: Minn. Hist. Society, notes pg. 107

Monument: Set 1"x36" iron pipe with brass cap up 6", from remains of original witness tree and marked new witnesses as follows. 1/4 S9| S10 1930

Evidence of Subsequent Corner Restoration

Year of search 10/1934 By D.J. Sutton, Compassman CCC

Location filed: Form 874-9

Monument: Found brass cap iron pipe up 9" in good condition, placed a metal location poster on the NE BT and notes witnesses as follow.

Bearing Trees, Reference Objects

Species	<u>White Ash</u>	<u>Balsam</u>	_____
Diameter	<u>8"</u>	<u>5"</u>	_____
Bearing	<u>N 64 1/2° E</u>	<u>N 44 1/2° W</u>	_____
Distance	<u>41 links</u>	<u>6 links</u>	_____

Bearing Trees, Reference Objects

Species	<u>Ash</u>	<u>Balsam(dead)</u>	_____
Diameter	<u>8"(1930)</u>	<u>4"(1930)</u>	_____
Bearing	<u>N 65°15' E</u>	<u>N 42°30' W</u>	_____
Distance	<u>40 links</u>	<u>7 links</u>	_____

Subsequent Corner Restoration

Year surveyed Circ 1960 By Miley & Wolters

Location filed: USFS Book 1, page 38, 5680-11

Monument: Found GLO iron pipe with brass cap Steel Sign Post, North, 2.0'

3/1983, C.R. Krause, USFS  
USFS Book 1, page 38  
Found GLO 1" iron pipe with brass cap, up 10" in good condition, needs witnesses. Loop road comes from FR 2135, approx. 150' S., Timber sale completed, no danger of damage.

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Location filed: \_\_\_\_\_

Monument: \_\_\_\_\_

