


T. 144 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N 1/4 19 Corner common to sections 18, 19



● = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search 1930 by Craig  
Monument found \_\_\_\_\_  
Minn. Hist. Society, notes pg. 142

Bearing Trees

Species	<u>Sugar</u>	<u>Burr Oak</u>
Diameter	<u>6"</u>	<u>16"</u>
Bearing	<u>N 6° E</u>	<u>S 73° W</u>
Distance	<u>21 links</u>	<u>49 links</u>

Original Bearing Trees Found

Species	<u>Burr Oak</u>
Diameter	<u>28"</u>
Bearing	<u>S 73° W</u>
Distance	<u>49 links</u>

Subsequent Corner Restoration

Year surveyed 7/1930 By H.D. Craig, US Surveyor  
Location filed: Minn. Hist. Society, notes pg. 142 1/4 S18  
Monument: Set 1"x36" iron pipe with brass cap S19  
up 6", from original witness tree, corner falls 1930  
on E. edge of old Rail Road grade, N. to S. and  
marked new witnesses as follows.

Evidence of Subsequent Corner Restoration

Year of search 10/1931 By K. Schulte, Estimator CCC  
Location filed: Form 874-9  
Monument: Found brass capped pipe  
up 7" in good condition, placed a metal location poster on the  
SW witness tree and notes witnesses as follow.

Bearing Trees, Reference Objects

Species	<u>Burr Oak</u>	<u>Birch</u>
Diameter	<u>28"(GLO)</u>	<u>4"</u>
Bearing	<u>S 73° W</u>	<u>N 62° E</u>
Distance	<u>49 links</u>	<u>42 links</u>

Bearing Trees, Reference Objects

Species	<u>White Oak</u>	<u>White Birch</u>
Diameter	<u>31"(1930)</u>	<u>4"</u>
Bearing	<u>S 65° W</u>	<u>N 55° E</u>
Distance	<u>48 links</u>	<u>43 links</u>

Subsequent Corner Restoration

Year surveyed 3/1975 By C.R. Krause, USFS  
Location filed: USFS Book 1, page 52  
Monument: Found GLO iron pipe with brass cap  
up 10" in good condition, 700'+/-, S. of Welch Lake Rd., 20' E.  
of old N. to S. grade and witnesses as follow.  
Large Oak stump, S 73° W, 32.3'(1930) rotted  
Birch stump, S 62° E, 27.7'(1930) rotted  
11" Red Oak, North, 51.85' scribed  
15" Red Oak, N 76° W, 48.3' scribed  
8" White Pine, S 89° E, 88.0' scribed  
11" Basswood, S 46° E, 9.9' scribed  
Steel Sign Post, West, 54-4 sign  
10" Red Oak, South, 3.0' FSLP


Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Index No. N3

CASS COUNTY LAND CORNER RECORD

T. 144 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N1/4 19 Corner common to sections 18, 19



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species Sugar Br. Oak \_\_\_\_\_  
Diameter 6" 16" \_\_\_\_\_  
Bearing N6E S73W \_\_\_\_\_  
Distance 21 LKS 49 LKS \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1930 By GLO  
Location filed Sec. of State  
Monument Find SW BIT - now 28" Set 1x36" 1/4 P.  
W/brass cap  
Cor. falls on E. Edge of old R.R. 1/4 S18  
519  
1930

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Bearing Trees, Reference Objects

Species Birch remark \_\_\_\_\_  
Diameter 4" S.W. \_\_\_\_\_  
Bearing N62E BIT. \_\_\_\_\_  
Distance 42 LKS \_\_\_\_\_

Bearing Trees, Reference Objects

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - MILO STEFAN - 1975 FILED IN 1980  
Doc. # 258592  
Found GLO monument in good condition  
11" Red Oak North 51.85';  
15" Red Oak N76W 48.30';  
8" W. Pine S89E 88.00';  
11" Basswood S46E 9.90'

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_