


T. 144 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
C.S. 1/16 Corner common to sections 27



EXISTING SURVEYS

Original Government Survey

Year surveyed 6/1930, H.D. Craig, US Surveyor S 1/16 <sup>C</sup> S27  
Original monument Set 1"x 36" iron pipe w/brass cap <sub>C</sub>  
1930

Original Evidence Found

Year of search \_\_\_\_\_ by \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>Birch</u>	<u>Cedar</u>	_____
Diameter	<u>6"</u>	<u>6"</u>	_____
Bearing	<u>S 33 1/2° E</u>	<u>S 45 1/2° W</u>	_____
Distance	<u>42 links</u>	<u>37 links</u>	_____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 10/1934 By G. Ryes, Estimator CCC  
Location filed: Form 874-9  
Monument: Found Metal hub  
up 7" in good condition and the following witnesses.

Evidence of Subsequent Corner Restoration

Year of search 1968 By L. Martinson, USFS  
Location filed: USFS, Certificate of Location  
Monument: Found brass cap monument

Bearing Trees, Reference Objects

Species	<u>Cedar</u>	<u>White Birch</u>	_____
Diameter	<u>6"(1930)</u>	<u>6"(1930)</u>	_____
Bearing	<u>S 45° W</u>	<u>S 42° E</u>	_____
Distance	<u>27'</u>	<u>24'</u>	_____

Bearing Trees, Reference Objects

Species	<u>Cedar</u>	_____	_____
Diameter	<u>12"(1930)</u>	_____	_____
Bearing	<u>S 46° W</u>	_____	_____
Distance	<u>24.4'</u>	_____	_____

Subsequent Corner Restoration

Year surveyed 1/1981 By G. Brama, USFS  
Location filed: USFS Book 1, page 13  
Monument: Found iron pipe  
bent, straighten pipe, 30' W. of woods trail and notes  
witnesses as follow.  
15" Cedar, S 46° W, 24.4' (1930)  
17" Yellow Birch, N 50° E, 75.4' marked CS 1/16 S27 BT  
15" Yellow Birch, S 62° E, 76.48' marked CS 1/16 S27 BT  
Steel Sign Post, East, 1.5'  
  
9/1982, G.H. Stevenson, LS 12684  
Certificate of Location  
Found GLO brass cap monument and 1981 witnesses.


Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed: \_\_\_\_\_  
Monument: \_\_\_\_\_

Index No. U 15

CASS COUNTY LAND CORNER RECORD

T. 144 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
C.S. 116 Corner common to sections 27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1930  
Original monument 1x36" I.P.W. brass S 1/161 527  
cap 1930

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees	
Species <u>Birch</u>	<u>Cedar</u>
Diameter <u>6"</u>	<u>6"</u>
Bearing <u>S 33 1/2 E</u>	<u>S 45 1/2 W</u>
Distance <u>42 LKS</u>	<u>37 LKS</u>

Original Bearing Trees Found			
Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - Gary Stevenson - 1982  
Doc. # 264959  
Found GLO monument in good condition  
15" Cedar S 46 W 24.4' (1930 BT);  
17" Y. Birch N 50 E 75.4';  
15" Y. Birch S 68 E 76.48'

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_