


Index No. V11

CASS COUNTY LAND CORNER RECORD

T. 144 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
N1/4 33 Corner common to sections 28, 33



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1873  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	<u>Cedar</u>	<u>Trim</u>		
Diameter	<u>6"</u>	<u>8"</u>		
Bearing	<u>S31E</u>	<u>N42E</u>		
Distance	<u>15 LKS</u>	<u>16 LKS</u>		

Original Bearing Trees Found

Species				
Diameter				
Bearing				
Distance				

Subsequent Corner Restoration

Year surveyed 1930 By GLD  
Location filed Sec of State  
Monument End NE BIT - (Dead) Set 1x36" 1/4 Pin w/ brass cap  
114 528  
114 533  
1930

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Bearing Trees, Reference Objects

Species	<u>Cedar</u>	<u>Cedar</u>		
Diameter	<u>6"</u>	<u>6"</u>		
Bearing	<u>S87 1/2 W</u>	<u>N32 1/2 W</u>		
Distance	<u>17 LKS</u>	<u>22 LKS</u>		

Bearing Trees, Reference Objects


Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_