


T. 144 R. 30 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

NE 31 Corner common to sections 29, 30, 31, 32



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search 1930 by Craig  
Monument found \_\_\_\_\_  
Minn. Hist. Society, notes pg 126

Bearing Trees

Species	Aspen	Aspen	White Pine	Aspen
Diameter	12"	8"	14"	10"
Bearing	N 35° E	S 45° E	N 47° W	S 10° W
Distance	13 links	60 links	63 links	48 links

Original Bearing Trees Found

Species	Badly rotted	Stump	White Pine
Diameter	Poplar stump	hole	24" stump
Bearing	N 54 1/4° E	S 10 1/2° W	N 54° W
Distance	13 links	48 links	63 links

Subsequent Corner Restoration

Year surveyed 7/1930 By H.D. Craig, US Surveyor  
Location filed: Minn. Hist. Society, notes pg 126 T144N R30W  
Monument: Set 2"x36" iron pipe with brass cap S30 | S29  
up 6", from remains of original witnesses and S31 | S32  
marked new witnesses trees as follows. 1930

Evidence of Subsequent Corner Restoration

Year of search 10/1934 By D.J. Sutton, Compassman, CCC  
Location filed: Form 874-9  
Monument: Found 1" pipe with brass cap  
up 4", in good condition, placed FSLP on NE Elm witness and  
notes witnesses as follows.

Bearing Trees, Reference Objects

Species	Elm	Poplar	Birch	Elm
Diameter	12"	4"	6"	10"
Bearing	N 48 1/2° E	S 15° E	S 17° W	N 67 1/4° W
Distance	29 links	23 links	45 links	76 links

Bearing Trees, Reference Objects

Species	Elm	Birch	White Pine stp
Diameter	13"(1930)	7"(1930)	30"(GLO)
Bearing	N 48°15' E	S 15° W	N 55° W
Distance	29 links	44 links	61 links

Subsequent Corner Restoration

Year surveyed 3/1975 By C.R. Krause, USFS  
Location filed: USFS Book 2, page 5  
Monument: Found 2" iron with brass cap  
up 4", in good condition, 400' S. of woods trail and witnesses.  
Rotted stump, N 54° W, 41.6'(GLO)  
15" Elm, N 49° E, 19.1'(1930) scribe overgrown  
Rotted stump, S 15° E, 15.2'(1930)  
10" Birch, S 17° W, 29.7'(1930) scribe overgrown  
15" Elm, N 68° W, 50.2'(1930) scribe overgrown  
10" White Pine, N 2° E, 111.2' scribed T144N R30W S29 BT  
9" White Pine, N 27° W, 143.9' scribed T144N R30W S30 BT  
12" Elm, S 40° W, 48.8' scribed T144N R30W S31 BT  
25" White Pine, S 10° E, 140.2' scribed T144N R30W S32 BT  
Steel Sign Post, South, 3.9' 54-2 and 54-4 signs  
Steel Sign Post, North, 3.5' 54-2 sign


Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed: \_\_\_\_\_  
Monument: \_\_\_\_\_

Index No. V5

CASS COUNTY LAND CORNER RECORD

T. 144 R. 30 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 31 Corner common to sections 29, 30, 31, 32



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing	Trees	Distance
<u>Aspen</u>	<u>Aspen</u>	<u>Willow</u>	<u>Aspen</u>
<u>12"</u>	<u>8"</u>	<u>14"</u>	<u>10"</u>
<u>N35E</u>	<u>S45E</u>	<u>N47W</u>	<u>S10W</u>
<u>13 LKS</u>	<u>60 LKS</u>	<u>63 LKS</u>	<u>48 LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1930 By GLO  
Location filed SEC OF STATE  
Monument Find stumps of NE, NW & SW BITS. Set 2536'  
1/4 NW 1/4 cross cap T144N R30W  
530 | 529  
531 | 532

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_

Bearing Trees, Reference Objects

Species	Bearing	Trees	Reference Objects	Distance
<u>Elm</u>	<u>Poplar</u>	<u>Birch</u>	<u>Elm</u>	<u>1930</u>
<u>12"</u>	<u>4"</u>	<u>6"</u>	<u>10"</u>	
<u>N48 1/2 E</u>	<u>S15E</u>	<u>S17W</u>	<u>N67 3/4 W</u>	
<u>29 LKS</u>	<u>23 LKS</u>	<u>45 LKS</u>	<u>76 LKS</u>	

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
CERTIFICATE - MILO STEFAN - 1975 - FILED IN 1980  
Doc. # 258591  
Found GLO monument in good condition  
10" W. PINE N2E 111.80';  
9" W. PINE N27W 143.90';  
12" Elm S40W 48.80';  
25" W. PINE S10E 140.20'

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_