


Index No. B.2-21.0

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

MC #17 Corner common to sections 1, 2



● = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search 1930 by Craig  
Monument found \_\_\_\_\_  
Notes page 46

Bearing Trees

Species	<u>Norway Pine</u>	<u>Birch</u>	_____
Diameter	<u>30"</u>	<u>3"</u>	_____
Bearing	<u>S 4° E</u>	<u>S 2° W</u>	_____
Distance	<u>206 links</u>	<u>2 links</u>	_____

Original Bearing Trees Found

Species	<u>Norway Pine</u>	_____	_____
Diameter	<u>28" stump</u>	_____	_____
Bearing	<u>S 4° E</u>	_____	_____
Distance	<u>206 links</u>	_____	_____

Subsequent Corner Restoration

Year surveyed 9/1930 By H.D. Craig, U.S. Surveyor, GLO  
Location filed: MN Historical Society, notes page 46 MC  
Monument: Set 1"x 36" I.P. with brass cap S2 | S1  
from remains of original bearing tree, up 6" T144N R31W  
and witnessed as follows. 1930

Evidence of Subsequent Corner Restoration

Year of search 1/1986 By C. Krause, USFS  
Location filed: T144N R31W Field Book 1, page 42  
Monument: Found 1" iron pipe with brass cap  
in ice at lake shore, 2' below bank, N. of ice ridge. Notes 1930  
witnesses as follows.

Bearing Trees, Reference Objects

Species	<u>Norway Pine</u>	<u>Birch</u>	_____
Diameter	<u>26"</u>	<u>6"</u>	_____
Bearing	<u>S 27 1/2° E</u>	<u>S 11° W</u>	_____
Distance	<u>147 links</u>	<u>5 links</u>	_____

Bearing Trees, Reference Objects

Species	<u>N. Pine stp</u>	<u>Birch snag</u>	_____
Diameter	<u>26"</u>	<u>7"x 5'</u>	_____
Bearing	<u>S 28° E</u>	<u>S 11° W</u>	_____
Distance	<u>97.0'</u>	<u>3.3'</u>	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed: \_\_\_\_\_  
Monument: \_\_\_\_\_


Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed: \_\_\_\_\_  
Monument: \_\_\_\_\_

Index No. B-C 21

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 574 Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
MC # 17 Corner common to sections 1, 2



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees  
Species NiPine Birch \_\_\_\_\_  
Diameter 30" 3" \_\_\_\_\_  
Bearing 54E 52W \_\_\_\_\_  
Distance 206 LKS 2 LKS \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed 1930 By GLD  
Location filed Sec. of State  
Monument End Stump of F SE B.T. Set 1x36" 1lb.  
w/brass cap

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_

Bearing Trees, Reference Objects

Species NiPine Birch \_\_\_\_\_  
Diameter 26" 6" \_\_\_\_\_  
Bearing 52 1/2 E 51 W \_\_\_\_\_  
Distance 147 LKS 5 LKS \_\_\_\_\_

Bearing Trees, Reference Objects

\_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
Filed at \_\_\_\_\_ Date \_\_\_\_\_