


T. 144 R. 31 M. 5th Coordinates: X _____ Y _____
E 1/4 Corner common to sections 4,5



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
Original monument Post

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species	<u>Balsam</u>	<u>Balsam</u>
Diameter	<u>4"</u>	<u>4"</u>
Bearing	<u>N 25° W</u>	<u>N 78° E</u>
Distance	<u>5 links</u>	<u>22 links</u>

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1925 By Minn Hwy Dept.
Location filed: R/W map Walker to Cass Lake
Monument: Rail road angle bar
400.8' E. of centerline.

Evidence of Subsequent Corner Restoration

Year of search 5/2007 By CCHD/SO
Location filed: #2002.022
Monument: Found Angle Iron
up 0.1', 415'+- east of Highway #371.

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

Species	<u>Balsam</u>	<u>B. Oak</u>	<u>B. Oak</u>
Diameter	<u>6"</u>	<u>6"</u>	<u>10"</u>
Bearing	<u>N 48° W</u>	<u>S 48° W</u>	<u>S 20° W</u>
Distance	<u>28.48'</u>	<u>21.47'</u>	<u>34.54'</u>

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed: _____
Monument: _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed: _____
Monument: _____

