

Index No. _____

CASS COUNTY LAND CORNER RECORD

T. _____ R. _____ M. _____ Coordinates: X _____ Y _____

Corner common to sections _____



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed _____
Original monument _____

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species _____
Diameter _____
Bearing _____
Distance _____

Original Bearing Trees Found

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:

Evidence of Subsequent Corner Restoration

Year of search _____ By _____
Location filed:
Monument:

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Bearing Trees, Reference Objects

Species _____
Diameter _____
Bearing _____
Distance _____

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed:
Monument:


Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed:
Monument:

Index No. E 5

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 5TH Coordinates: X 394400.84 Y 284308.97
NE 7 Corner common to sections 5, 6, 7, 8



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875

Original monument Post

Bearing Trees

Species	<u>w. line</u>	<u>w. line</u>	<u>w. line</u>	<u>w. line</u>
Diameter	<u>28"</u>	<u>26"</u>	<u>26"</u>	<u>26"</u>
Bearing	<u>N45E</u>	<u>N45W</u>	<u>S28W</u>	<u>S32E</u>
Distance	<u>61KS</u>	<u>10KS</u>	<u>61KS</u>	<u>50KS</u>

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1913 By JOHN CURD

Location filed COUNTY SURVEY RECORD BOOK B P. 36-39

Monument END WOOD STAKE SET BY 48" GALV. IIP W/ CAP. OLD BITS. CHECK.

Evidence of Subsequent Corner Restoration

Year of search 1910 By JAMES MIDDLETON

COUNTY BOOK B P. 57B TWO POST SET FROM OLD GOVT BITS:
STUMP 28" W. LINE N45E 61KS, STUMP 26" W. LINE N45W 10KS,
STUMP 26" W. LINE S28W 61KS, 26" W. LINE S32E 50KS, AND
Co. Rd. SURVEY BITS: 12" BASSWOOD N 80-05W 49.22', 6" OAK HUB
S52-12E 62.00', 6" OAK HUB S24-47W 66.51'

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

E-5

Subsequent Corner Restoration E 5

Year surveyed 1990 By WALT CURD

Location filed _____

Monument END 1" IRON PIPE IN E. E. OF
Co. Rd. SET 3/4" IRON PIN ON TOP &
DRIVE IT DOWN 2" BELOW SURFACE

<u>TOP R. OAK</u>	<u>R. OAK</u>	<u>R. OAK</u>
<u>14"</u>	<u>16"</u>	<u>14"</u>
<u>N30W</u>	<u>S60E</u>	<u>S45W</u>
<u>99.70</u>	<u>99.40</u>	<u>113.50</u>

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

CE'RT. BY WALT CURD 1990
DOC. # 325736

4/2001 USFS crew found 1990
BT's alive and metal detector
draw in road.

4/2002 CCSO found 60d spike in
Q & R at intersection of 1990 witness
GPS location see file #2002.009.