


T. 144 R. 31 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

E 1/16 Corner common to sections 13, 24



EXISTING SURVEYS

Original Government Survey

Year surveyed 9/1930, H.D. Craig, U.S. Surveyor, GLO S 25  
 Original monument Set 1"x 3' iron pipe w/brass cap E1/16 S 36  
 Notes page 19, at proportionate distance and witnessed 1930

Bearing Trees

Species	<u>Poplar</u>	<u>White Oak</u>	_____
Diameter	<u>5"</u>	<u>10"</u>	_____
Bearing	<u>N 21 1/2° W</u>	<u>S 39 3/4° W</u>	_____
Distance	<u>14 links</u>	<u>94 links</u>	_____

Original Evidence Found

Year of search \_\_\_\_\_ by \_\_\_\_\_  
 Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 8/1963 By W.H. Okerman, LS 6807  
 Location filed: USFS Field Book 1, page 17  
 Monument: Found GLO pipe with brass cap and witnessed as follows.

Bearing Trees, Reference Objects

Species	<u>White Pine</u>	<u>Maple</u>	<u>Steel Sign</u>	_____
Diameter	<u>18"</u>	<u>8"</u>	<u>Post</u>	_____
Bearing	<u>S 80° W</u>	<u>N 5° W</u>	<u>N 66° E</u>	_____
Distance	<u>71.1'</u>	<u>24.1'</u>	<u>7.35'</u>	_____

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Location filed: \_\_\_\_\_  
 Monument: \_\_\_\_\_

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed: \_\_\_\_\_  
 Monument: \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Location filed: \_\_\_\_\_  
 Monument: \_\_\_\_\_

