


T. 144 R. 31 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 24 Corner common to sections 25, 36 and 30, 31-144-30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ by \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species	Red Oak	Sugar	Red Oak	Aspen
Diameter	10"	6"	4"	8"
Bearing	S 10° E	N 60° E	S 53° W	N 32° W
Distance	18 links	22 links	47 links	27 links

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 4/1930 By H.D. Craig, U.S. Surveyor, GLO  
Location filed: MN Hist. Soc., 144-30 notes pg 22 T144N  
Monument: Set 2"x 3' iron pipe. w/brass cap R31W | R30W  
at proportionate distance, up 6", and marked S25 | S30  
new witnesses as follows. S36 | S31  
1930

Evidence of Subsequent Corner Restoration

Year of search 8/1934 By D.J. Sutton, Compassman, CCC  
Location filed: USFS Form 874-9  
Monument: Found Brass capped 1" Iron pipe up 2", in good condition.

Bearing Trees, Reference Objects

Species	Poplar	Poplar	Birch	Poplar
Diameter	5"	5"	4"	5"
Bearing	N 11 3/4° E	S 66° E	S 62° W	N 49 1/2° W
Distance	18 links	13 links	12 links	33 links

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 10/1975 By C.R. Krause, USFS  
Location filed: USFS 144-30 Field Book 2, page 32  
Monument: Found GLO 2" iron pipe with brass cap up 3", 625' N. of woods trail and witnesses as follows.  
Poplar stump, N 12° E, 11.9'(1930)  
11" Birch, S 62° W, 7.9'(1930) no scar visible  
16" Red Oak, N 75° E, 51.3' nail and tag  
7" Basswood, N 74° W, 34.7' nail and tag  
9" Red Oak, S 51° W, 20.2' nail and tag  
6" Maple, S 33° E, 9.2' nail and tag  
Steel Sign Post, West, 2.0' 54-9 sign  
3" Ironwood, South, 625' FSLP, N. side FW #29

Evidence of Subsequent Corner Restoration Found


Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Index No. V 25

CASS COUNTY LAND CORNER RECORD

T. 144 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

NE 36 Corner common to sections 25, 36 AND 30, 31 - 144-30



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing	Trees	Distance
<u>R. oak</u>	<u>Sugar</u>	<u>R. oak</u>	<u>Aspen</u>
<u>10"</u>	<u>6"</u>	<u>4"</u>	<u>8"</u>
<u>S10E</u>	<u>N60E</u>	<u>S53W</u>	<u>N32W</u>
<u>18LKS</u>	<u>22LKS</u>	<u>47LKS</u>	<u>27LKS</u>

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

O = Corner

Subsequent Corner Restoration

Year surveyed 1930 By GLD  
Location filed Sec. of State  
Monument Set 2x36" l.p. w/ brass cap

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_

7144N  
R31W R30W  
S25 / S30  
S36 / S31

Bearing Trees, Reference Objects

Species	Bearing	Trees	Reference Objects	Distance
<u>Poplar</u>	<u>Poplar</u>	<u>Birch</u>	<u>Poplar</u>	<u>1930</u>
<u>5"</u>	<u>5"</u>	<u>4"</u>	<u>5"</u>	
<u>N17 1/2 E</u>	<u>S66 E</u>	<u>S62 W</u>	<u>N49 1/2 W</u>	
<u>18LKS</u>	<u>13LKS</u>	<u>12LKS</u>	<u>33LKS</u>	

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_