


T. 145 R. 28 M. 5TH Coordinates: X SE 36 Y Corner common to sections 36 AND 31-145-27



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871
 Original monument bst

Bearing Trees

Species	<u>Y. Pine</u>	<u>Y. Pine</u>	_____
Diameter	<u>1 1/2"</u>	<u>6"</u>	_____
Bearing	<u>N 35 W</u>	<u>N 20 E</u>	_____
Distance	<u>60 LKS</u>	<u>43 LKS</u>	_____

Original Evidence Found

Year of search _____ By _____
 Monument found _____

Original Bearing Trees Found

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1912 By John Curd
 Location filed COUNTY SURVEY RECORD BOOK "A" P 544-550
 Monument FIND OLD COIN BITS; 6" Y. PINE N 20 E 43 LKS, 1 1/2" Y. PINE N 35 W 60 LKS SET 2 1/2 X 4 8" GALV. I.P. W/ 3" CAP W/ 1 1/2" X 2 4" ROD AS ANCHOR ON BOTTOM

Evidence of Subsequent Corner Restoration

Year of search _____ By _____

Bearing Trees, Reference Objects

Species	_____	_____	_____
Diameter	_____	_____	_____
Bearing	_____	_____	_____
Distance	_____	_____	_____

Bearing Trees, Reference Objects

_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed _____ By _____
 Location filed _____
 Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

Certificates - Ken Whitehorn - USFS - 1984
Doc. # 274372
Found 7" concrete monument with GLO brass cap, and a 2 1/2" iron pipe with well cap.
20" pine stump N 34 W 39.54';
10 1/2" Red Oak N 18 W 33.18';
23" Red Pine N 25 E 28.39';
13 1/2" Red Oak N 88 1/2 W 11.90';
8" W. Pine N 70 E 15.60';
8 1/2" spruce S 75 1/2 E 27.94'