


T. 145 R. 30 M. 5th Coordinates: X _____ Y _____

NE 34 Corner common to sections 26, 27, 34, 35



EXISTING SURVEYS

Original Government Survey

Year surveyed 1874
Original monument Post

Original Evidence Found

Year of search _____ by _____
Monument found _____

Bearing Trees

Species	<u>Elm</u>	<u>Linden</u>	_____	_____
Diameter	<u>6"</u>	<u>8"</u>	_____	_____
Bearing	<u>N 27° W</u>	<u>N 13° E</u>	_____	_____
Distance	<u>30 links</u>	<u>75 links</u>	_____	_____

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 7/1933 By W.W. Bandy, Surveyor, GLO
Location filed: MN Historical Society, Notes pg 43 T145N R30
Monument: Set 6" conc. cylinder with brass tablet S 27 | S 26
at intersection of the original blazed lines, up 3" S 34 | S 35
and witnessed as follows. 1933
14" Basswood, S 36 1/4° E, 70 links(46.20') by local Surveyor

Evidence of Subsequent Corner Restoration

Year of search 8/1934 By C.J. Mendenhall, Compassman
Location filed: USFS Form 874-9
Monument: Brass cap on cement up 3" and witnesses as follows.

Bearing Trees, Reference Objects

Species	<u>White Pine</u>	<u>Poplar</u>	<u>Balsam</u>	<u>White Pine</u>
Diameter	<u>8"</u>	<u>10"</u>	<u>8"</u>	<u>7"</u>
Bearing	<u>N 51 1/2° E</u>	<u>S 51° E</u>	<u>S 27 1/2° W</u>	<u>N 88 1/4° W</u>
Distance	<u>48 links</u>	<u>14 links</u>	<u>65 links</u>	<u>78 links</u>

Bearing Trees, Reference Objects

Species	<u>White Pine</u>	<u>Aspen</u>	<u>Balsam</u>	<u>White Pine</u>
Diameter	<u>6"</u>	<u>10"</u>	<u>6"</u>	<u>10"</u>
Bearing	<u>N 52° E</u>	<u>S 50°30' E</u>	<u>S 26°15' W</u>	<u>N 89°15' W</u>
Distance	<u>46 links</u>	<u>13.2 links</u>	<u>63.8 links</u>	<u>77 links</u>

Subsequent Corner Restoration

Year surveyed 9/1976 By C.R. Krause, USFS
Location filed: USFS Book 2, page 40
Monument: Found GLO concrete with brass tablet up 5", in good condition, and witnessed as follows.
White Pine, N 52° E, 31.6'(1933) wind fall
20" W. Pine stump, N 88° W, 51.5'(1933) scribe inside
8" White Oak, S 36° W, 80.30' marked
8" Elm, S 73° E, 76.45' marked
10" Ash, N 69° E, 39.30' marked
9" Ash, N 47° W, 48.35' marked
11" Birch, East, 8.0' Found FSLP
10" Birch, N 50° W, 5.0' add FSLP
Steel Sign Post, West, 1.2' FS 54-4 sign

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
Location filed: _____
Monument: _____

