


T. 145 R. 31 M. 5th Coordinates: X _____ Y _____

NE 2 Corner common to sections 1, 2 and 35, 36-146-31



● = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
Original monument Post

Original Evidence Found

Year of search 1900 by COE
Monument found _____
Lake Winnebigoishish Reservoir

Bearing Trees

Species	<u>White Pine</u>	<u>Burr Oak</u>	<u>Burr Oak</u>	<u>White Oak</u>
Diameter	<u>24"</u>	<u>10"</u>	<u>10"</u>	<u>7"</u>
Bearing	<u>S 11° E</u>	<u>S 37° W</u>	<u>N 68° W</u>	<u>N 24° E</u>
Distance	<u>42 links</u>	<u>34 links</u>	<u>17 links</u>	<u>43 links</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1904 By T.M. Fowble
Location filed: Lake Winnebigoishish Reservoir
Monument:
Indicates known corner

Evidence of Subsequent Corner Restoration

Year of search 6/1918 By W.E. La Fountain
Location filed: Plat Ah-nung-Point, Doc. #52740
Monument:
Indicates corner on Plat

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 4/1931 By J.M. Greene
Location filed: Curo Book 61, image 111
Monument: Set wooden hub from Dead GLO W. Pine and Green GLO Burr Oak, NW.

Evidence of Subsequent Corner Restoration Found

Year of search 10/1965 By J. Ekstrom, USFS
Location filed: T145N R31W Field Book 1, page 2 T146N R31W
Monument: Found brass cap cut off, 1/2 still in S35 | S36
he set a 2" USFS monument with brass cap S2 | S1
12" Oak, N 37° E, 40.26'(1933) scribe over grown T145N
Oak snag, S 56° E, 35.64'(1933) 1965
8" Oak, S 49° W, 27.72'(1933) RLS No 6807
6" Oak, S 16° E, 24.9' scribed
13" Oak, S 75° W, 53.2' scribed
13" Oak, N 18° W, 36.2' scribed
9" Oak, N 55° E, 28.9' scribed

7/1933, H.D. Craig, U.S. Surveyor
Minnesota Historical Society T146N R31W
Set 6" concrete Cylinder with brass cap S35 | S36
from the NW and SW GLO witness trees S2 | S1
and the remains of the NE and SE witnesses. T145N
14" Burr Oak, N 68° E, 17 links(11.22') GLO 1933
12" Burr Oak, S 37° W, 34 links(22.44') GLO
8" Oak, N 37° E, 61 links(40.26')
8" Oak, S 56° E, 54 links(35.64')
6" Oak, S 49° W, 42 links(27.72')


5/1936, CCC
USFS, Form 874-9
Indicates the following witnesses.
28" W. P. on sec 1 scribed
14" oak on sec 2 scribed
14" oak on sec 35 scribed

4/2004, R. Main, USFS
T145N R31W Field Book 1, page 2
Found USFS brass cap. Locate with GPS, 15'+/- S. of Woods
Rd., 50'+/- N. of Power line and witnesses.
17" W. Oak, N 37° E, 40.26'(1933)
8" Oak, S 49° W, 27.72'(1933) 15' snag
20" W. Oak, S 75° W, 53.2'
17" W. Oak, N 18° W, 36.2'

Index No. A 21

CASS COUNTY LAND CORNER RECORD

T. 145 R. 31 M. 5TH Coordinates: X _____ Y _____
NE 2 Corner common to sections 1, 2



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875
Original monument Post

Original Evidence Found

Year of search _____ By _____
Monument found _____

	Bearing Trees			
Species	<u>White</u>	<u>Br Oak</u>	<u>Br. oak</u>	<u>W. Oak</u>
Diameter	<u>24"</u>	<u>10"</u>	<u>10"</u>	<u>7"</u>
Bearing	<u>S11E</u>	<u>S37W</u>	<u>N68W</u>	<u>N24E</u>
Distance	<u>42LKS</u>	<u>34LKS</u>	<u>17LKS</u>	<u>43LKS</u>

Original Bearing Trees Found

Species	_____	_____	_____	_____
Diameter	_____	_____	_____	_____
Bearing	_____	_____	_____	_____
Distance	_____	_____	_____	_____

O = Corner

Subsequent Corner Restoration

Year surveyed 1933 By GLO
Location filed Sec. of State
Monument End NW & SW BITS - now 14" x 12" - and remains
of NE & SE BITS - set concrete man 20" long 6" dia
with brass cap 7146 N R 31 W

Evidence of Subsequent Corner Restoration

Year of search 1931 ? By John Greene
microfilm - roll 105 BK 61 P. 62
End B.T.S. Dead Pine S11E 42 LKS, Green Br. oak
N68W 17 LKS - set hub

Bearing Trees, Reference Objects

	Bearing Trees, Reference Objects			
Species	<u>Br. oak</u>	<u>Br oak</u>	<u>Br oak</u>	<u>remark SW</u>
Diameter	<u>8"</u>	<u>8"</u>	<u>6"</u>	<u>in NW BITS</u>
Bearing	<u>N37 1/2 E</u>	<u>S56 E</u>	<u>S49 1/2 W</u>	
Distance	<u>61 LKS</u>	<u>54 LKS</u>	<u>42 LKS</u>	

Bearing Trees, Reference Objects

_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

A-21

Subsequent Corner Restoration

Year surveyed _____ By _____
Location filed _____
Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____
PLAT - AH - BRING - POINT
W. E LA FOUNTAIN 1918

CERTIFICATE - BILL OKERMAN - 1965
Set 2" x 5' steel pipe with 3" stamped
bronze tablet.
6" Oak S16E 24.9';
13" Oak S75W 53.2';
13" Oak N18W 36.2';
9" Oak NSSE 28.9'

Remonumentation certificate prepared _____

By _____

Filed at _____

Date _____