

T. 145 R. 31 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 14 Corner common to sections 11, 12, 13, 14



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search 1900 by COE  
Monument found \_\_\_\_\_  
Lake Winnebigoishish Reservoir

Bearing Trees

| Species  | <u>White Pine</u> | <u>Norway Pine</u> | <u>White Pine</u> | <u>White Pine</u> |
|----------|-------------------|--------------------|-------------------|-------------------|
| Diameter | <u>30"</u>        | <u>24"</u>         | <u>20"</u>        | <u>12"</u>        |
| Bearing  | <u>S 22° W</u>    | <u>N 39° W</u>     | <u>S 7° E</u>     | <u>N 48° E</u>    |
| Distance | <u>30 links</u>   | <u>28 links</u>    | <u>68 links</u>   | <u>68 links</u>   |

Original Bearing Trees Found

| Species  | _____ | _____ | _____ | _____ |
|----------|-------|-------|-------|-------|
| Diameter | _____ | _____ | _____ | _____ |
| Bearing  | _____ | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ | _____ |

Subsequent Corner Restoration

Year surveyed 1904 By T.M. Fowble  
Location filed: Lake Winnebigoishish Reservoir  
Monument:  
Indicates known corner

Evidence of Subsequent Corner Restoration

Year of search x/1934 By J.A. Gjelhaug, Eng. CCC  
Location filed: T145N R31W Field Bk 1, pg 1  
Monument: Found wood post and iron pipe witnesses as follows

Bearing Trees, Reference Objects

| Species  | _____ | _____ | _____ | _____ |
|----------|-------|-------|-------|-------|
| Diameter | _____ | _____ | _____ | _____ |
| Bearing  | _____ | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ | _____ |

Bearing Trees, Reference Objects

| Species  | <u>R. Oak</u>  | <u>R. Oak</u>      | <u>W. Oak</u>      | <u>R. Oak</u>       |
|----------|----------------|--------------------|--------------------|---------------------|
| Diameter | <u>4"</u>      | <u>4"</u>          | <u>4"</u>          | <u>4"</u>           |
| Bearing  | <u>N 55° W</u> | <u>N 60 1/2° E</u> | <u>S 88 1/2° E</u> | <u>S 12° W</u>      |
| Distance | <u>7 links</u> | <u>37 links</u>    | <u>39 links</u>    | <u>29 1/2 links</u> |

Subsequent Corner Restoration

Year surveyed 7/1964 By J. Ekstrom, USFS  
Location filed: T145N R31W Field Bk 1, pg 1 T146N R31W  
Monument: Set 6" USFS Conc. cyl. w/ brass cap S11 | S12  
from GLO Pine stumps and witnesses. S14 | S13  
GLO Pine stump, S 32° W, 30 links(19.8') 1964  
GLO Pine stump, S 7° E, 68 links(44.9') RLS No. 6807  
GLO Pine stump, N 45° E, 68 links(43.0')  
6" Oak, N 52° W, 7 links(5.5') 1934  
8" Oak, N 60°30' E, 37 links(24.4') 1934  
6" Oak, S 88°30' E, 39 links(25.7') 1934  
8" Oak, S 12° W, 29 1/2 links(19.5') 1934

Evidence of Subsequent Corner Restoration Found

Year of search 6/1971 By P.J. Meyer, LS 3628  
Location filed: Plat of Stony Point, Doc. #203480  
Monument: Iron Found at corner.  
5/1987, C. Krause, USFS  
T145N R31W Field Book 1, page 1  
Found USFS brass cap and witnesses.  
W. Pine stump, S 4° E, 44.2'(GLO) well rotted  
W. Pine stump, S 33° W, 19.8'(GLO) well rotted  
N. Pine stump, N 39° W, 24.4'(GLO) well rotted  
W. Pine stump, N 42° E, 43.0'(GLO) well rotted, nearly level  
9" R. Oak, N 58° E, 24.4'(1967) scribe closed  
7" W. Oak, N 89° E, 25.1'(1967) scribe closed  
10" R. Oak, S 14° W, 19.5'(1967) 30" high stub, scribe closed  
20" W. Pine, N 5° E, 53.15' spike and scribed  
4" W. Oak, S 41° E, 32.85' spike and X scribe  
13" N. Pine, S 6° E, 135.95' spike and scribed  
10" N. Pine, S 7° W, 100.25' spike and scribed  
Steel Sign Post, West, 3.35'  
Steel Sign Post, North, 3.75'

7/1966, W.H. Okerman, LS 6807  
Affidavit as to Location of Government Corner, #590258  
Filed on the above information.


6/1967, D.A. Crain, Cadastral Surveyor, BLM  
Minnesota Historical Society, Notes page 1, 2  
Found USFS concrete mon. up 24" and wood stake.  
GLO Pine stump, S 4°30' E, 67 links(44.22') mark not legible  
9" Oak, N 58°25' E, 37 links(24.4') marked BT  
8" Oak, N 87°00' E, 38 links(25.08') marked BT  
8" Oak, S 9°45' W, 29 links(19.14') marked BT  
8" Dead Oak, N 51°16' W, 9 links(5.94') marked BT  
Pits to northeast and southwest

3/2008, B.W. Skipton, LS 17768  
Certificate of survey for Bowley, #3863  
Indicates a Forest Service concrete monument in place.

Index No. J 21

CASS COUNTY LAND CORNER RECORD

T. 145 R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 14 Corner common to sections 11, 12, 13, 14



○ = Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

|          | Bearing Trees  |                |                |                |
|----------|----------------|----------------|----------------|----------------|
| Species  | <u>W. Pine</u> | <u>N. Pine</u> | <u>W. Pine</u> | <u>W. Pine</u> |
| Diameter | <u>30"</u>     | <u>24"</u>     | <u>26"</u>     | <u>12"</u>     |
| Bearing  | <u>S 22 W</u>  | <u>N 39 W</u>  | <u>S 7 E</u>   | <u>N 48 E</u>  |
| Distance | <u>30 LKS</u>  | <u>28 LKS</u>  | <u>68 LKS</u>  | <u>68 LKS</u>  |

Original Bearing Trees Found

| Species  | _____ | _____ | _____ | _____ |
|----------|-------|-------|-------|-------|
| Diameter | _____ | _____ | _____ | _____ |
| Bearing  | _____ | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ | _____ |

Subsequent Corner Restoration

Year surveyed 1967 By BLM  
Location filed SEC. OF STATE  
Monument Find old wood post & stump of SE BT. also find concrete mon 6" dia 2' above ground w/ brass cap 7145N R3W

Evidence of Subsequent Corner Restoration

Year of search 1964 By William OKerman  
Set 6" x 6" cylindrical concrete monument with 3" stamped bronze tablet. Rescribed 1934 BT's.

Bearing Trees, Reference Objects

|          | Bearing Trees, Reference Objects |               |                 |                  |
|----------|----------------------------------|---------------|-----------------|------------------|
| Species  | <u>Oak</u>                       | <u>Oak</u>    | <u>Oak</u>      | <u>dead oak</u>  |
| Diameter | <u>9"</u>                        | <u>8"</u>     | <u>8"</u>       | <u>8"</u>        |
| Bearing  | <u>N 58-25 E</u>                 | <u>N 87 E</u> | <u>S 9-45 W</u> | <u>N 51-16 W</u> |
| Distance | <u>37 LKS</u>                    | <u>38 LKS</u> | <u>29 LKS</u>   | <u>9 LKS</u>     |

Bearing Trees, Reference Objects

| Species  | _____ | _____ | _____ | _____ |
|----------|-------|-------|-------|-------|
| Diameter | _____ | _____ | _____ | _____ |
| Bearing  | _____ | _____ | _____ | _____ |
| Distance | _____ | _____ | _____ | _____ |

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed \_\_\_\_\_  
Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
PLAT - STONY POINT  
PETER J. MEYER 1971  
CERTIFICATE - BILL OKERMAN - 1964

Remonumentation certificate prepared \_\_\_\_\_

By \_\_\_\_\_

Filed at \_\_\_\_\_

Date \_\_\_\_\_