


Index No. \_\_\_\_\_

CASS COUNTY LAND CORNER RECORD

T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

Corner common to sections \_\_\_\_\_



= Corner

EXISTING SURVEYS

Original Government Survey

Year surveyed \_\_\_\_\_  
Original monument \_\_\_\_\_

Original Evidence Found

Year of search \_\_\_\_\_ by \_\_\_\_\_  
Monument found \_\_\_\_\_

Bearing Trees

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Original Bearing Trees Found

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Evidence of Subsequent Corner Restoration

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Bearing Trees, Reference Objects

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Bearing Trees, Reference Objects

Species \_\_\_\_\_  
Diameter \_\_\_\_\_  
Bearing \_\_\_\_\_  
Distance \_\_\_\_\_

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Index No. \_\_\_\_\_

CASS COUNTY LAND CORNER RECORD

T. \_\_\_\_\_ R. \_\_\_\_\_ M. \_\_\_\_\_ Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

Page \_\_\_\_\_ of \_\_\_\_\_

Corner common to sections \_\_\_\_\_


Subsequent Corner Restoration

Evidence of Subsequent Corner Restoration Found

Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed:  
Monument:

T. 14S R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
NE 18 Corner common to sections 7, 8, 17, 18



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875

Original monument Post

Species	Bearing	Trees
<u>J. Pine</u>	<u>J. Pine</u>	<u>J. Pine</u>
<u>14"</u>	<u>12"</u>	<u>9"</u>
<u>N58E</u>	<u>S5W</u>	<u>S3E</u>
<u>398 LKS</u>	<u>348 LKS</u>	<u>291 LKS</u>

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_

Monument found \_\_\_\_\_

Original Bearing Trees Found

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1906 By John Curo

Location filed COUNTY SURVEY RECORD BOOK P. 266-267

Monument Find old Govt Post and old Govt B.T.S: 14" J. Pine  
N56E 262.68', 12" J. Pine S5W 229.68', 9" J. Pine  
S3E 192.66', 16" J. Pine N3W 595.84'  
Set 2 x 36" I.P.

Evidence of Subsequent Corner Restoration

Year of search 1912 By Curo

COUNTY BOOK D" P. 147 CORNER GRADED OUT - RESET CORNER  
FROM NE, SE & SW B.T.S also find orig post  
Set good, big tamarac post

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>TACK IN SE. B.T.</u>	<u>6"</u>	<u>S3E</u>	<u>192.68'</u>
<u>TACK IN SW. B.T.</u>	<u>6"</u>	<u>S 5-17W</u>	<u>226.54'</u>
<u>J. Pine</u>	<u>6"</u>	<u>N85-38E</u>	<u>160.83'</u>

Subsequent Corner Restoration

Year surveyed \_\_\_\_\_ By \_\_\_\_\_

Location filed \_\_\_\_\_

Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found

Year of search 1993 10-29 By Robert Murray

found P.K. nail as set by MURRAY SURVEYING, INC  
in 1992. Removed monument.  
10-29-93 placed a MndOT cast iron monument.  
4-26-94 Cert. Filed by: Robert Murray, RLS  
15483; Doc #357118. Ties: NW side of Power  
Pole 531W 92.29, spike up 4'; NE Power  
Pole 525E 86.88, spike up 4ft.

JUN 1996 R. DONAGHUE  
PLAT 5 SHOWS MON FOUND