


T. 14S R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E1/4 16 Corner common to sections 15, 16



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875  
Original monument Post

Species	Bearing	Trees
<u>J Pine</u>	<u>J Pine</u>	
<u>10"</u>	<u>12"</u>	
<u>N60E</u>	<u>S76W</u>	
<u>12 LKS</u>	<u>30 LKS</u>	

Original Evidence Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Monument found \_\_\_\_\_

Species	Bearing	Trees
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Subsequent Corner Restoration

Year surveyed 1911 By JOHN CURO  
Location filed COUNTY SURVEY RECORD BOOK # 1280-281  
Monument Find 2" I.P. SET FROM OLD GOVT B.T.S.

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

Evidence of Subsequent Corner Restoration

Year of search 1925 By Miss. Hwy Dept.  
R/W map in Recorder's Office - Walker to Cass Lake  
3/4" iron pin

Bearing Trees, Reference Objects

Species	Bearing	Distance
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

L-13

Subsequent Corner Restoration

Year surveyed 3/2001 By CCSO  
Location filed file # 2001.006  
Monument Found USFS Brass cap, down 0.3'  
5'± W. of & CR#147. 1987 N. Pine  
witness good, add the following:

<u>P. Pole</u>	<u>N 82° W</u>	<u>33.71' *</u>
<u>16" W. Pole</u>	<u>S 41° E</u>	<u>48.62' *</u>
<u>Steel Sign Post</u>	<u>East</u>	<u>34.0'</u>

\* distance to double head nail

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
PLAT - WEST CASS LAKE  
JOHN CURO 1907

PLAT - ORIGINAL PLAT OF CASS LAKE  
B.B. BARTLETT 1899

PLAT - LYOLCK'S ADDITION TO WEST CASS LAKE  
JOHN CURO 1907

Certificate - William Okerman - 1987

<u>Doc # 301740</u>	
<u>Find iron rod and ties at 2" x 2" I.P. w/cap</u>	
<u>18" J. Pine</u>	<u>S 24° E 84.71'</u>
<u>22" R. Pine</u>	<u>S 50° E 111.08'</u>
<u>CFP</u>	<u>N 73° E 38.86'</u>
<u>P.P.</u>	<u>N 83° W 33.65'</u>