


Index No. LS

CASS COUNTY LAND CORNER RECORD

T. 14S R. 31 M. 5TH Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_  
E 1/4 18 Corner common to sections 17, 18



EXISTING SURVEYS

Original Government Survey  
 Year surveyed 1875  
 Original monument Post

Original Evidence Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
 Monument found \_\_\_\_\_

Bearing Trees  
 Species N. Pine N. Pine  
 Diameter 24" 28"  
 Bearing West S89E  
 Distance 47LKS 30LKS

Original Bearing Trees Found  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Subsequent Corner Restoration  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration  
 Year of search 1994 3-14 By Robert Murray  
Placed 2' x 30' square tube w/ Mn DOT cast iron cap. Top of monument 0.5' above ground.  
4-26-94 Cert. Filed by Robert Murray, RLS  
15483, Doc # 357124

Bearing Trees, Reference Objects  
 Species \_\_\_\_\_  
 Diameter \_\_\_\_\_  
 Bearing \_\_\_\_\_  
 Distance \_\_\_\_\_

Bearing Trees, Reference Objects  
White Pine White Pine  
18" 17"  
N27W S47E  
29.27 55.06

Subsequent Corner Restoration  
 Year surveyed \_\_\_\_\_ By \_\_\_\_\_  
 Location filed \_\_\_\_\_  
 Monument \_\_\_\_\_

Evidence of Subsequent Corner Restoration Found  
 Year of search \_\_\_\_\_ By \_\_\_\_\_  
JUNE 1996 & DONAGHUE  
PLAT SHOWS MON FOUND

Remonumentation certificate prepared \_\_\_\_\_ By \_\_\_\_\_  
 Filed at \_\_\_\_\_ Date \_\_\_\_\_