


Index No. V11

CASS COUNTY LAND CORNER RECORD

T. 145 R. 31 M. 574 Coordinates: X _____ Y _____
N14 33 Corner common to sections 28, 33



EXISTING SURVEYS

Original Government Survey

Year surveyed 1875

Original monument lost

Species	Bearing	Trees
<u>W. Pine</u>	<u>12"</u>	<u>Aspen</u>
<u>12"</u>	<u>14"</u>	
<u>North</u>	<u>544W</u>	
<u>6 LKS</u>	<u>43 LKS</u>	

Original Evidence Found

Year of search _____ By _____

Monument found _____

Original Bearing Trees Found

Species	Diameter	Bearing	Distance

Subsequent Corner Restoration

Year surveyed 1925 By Minn. Hist Dept

Location filed R/W map in Recorder's office - Walker

Monument 1" iron pin to Cass Lake

Evidence of Subsequent Corner Restoration

Year of search 4/01 By CCSO

Found Alum cap tel spar, down 0.7',
6'± S. & CR #146, RLS 15483.

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance

10" W. Pine, N45°E, 84.09 to 60d spk BM

Bearing Trees, Reference Objects

Species	Diameter	Bearing	Distance
<u>W. Oak</u>	<u>16"</u>	<u>N2°E</u>	<u>41.41*</u>
<u>W. Oak</u>	<u>10"</u>	<u>S35°E</u>	<u>43.29*</u>
<u>Ash</u>	<u>8"</u>	<u>S27°E</u>	<u>57.54*</u>
<u>Ash</u>	<u>15"</u>	<u>S20°W</u>	<u>32.63'</u>

* distance to double head nail

Subsequent Corner Restoration

Year surveyed _____ By _____

Location filed _____

Monument _____

Evidence of Subsequent Corner Restoration Found

Year of search _____ By _____

June 1982 A. Kerick #12260

Cert. of Survey shows monument found

Remonumentation certificate prepared _____ By _____

Filed at _____ Date _____