


T. 145 R. 31 M. 5th Coordinates: X \_\_\_\_\_ Y \_\_\_\_\_

SE 34 Corner common to sections 34, 35 and 3-144-31



EXISTING SURVEYS

Original Government Survey

Year surveyed 1871  
Original monument Post

Original Evidence Found

Year of search 1900 by COE  
Monument found \_\_\_\_\_  
Lake Winnebigoishish Reservoir

Bearing Trees

Species	<u>Yellow Pine</u>	<u>Yellow Pine</u>
Diameter	<u>14"</u>	<u>20"</u>
Bearing	<u>N 53° E</u>	<u>N 5° W</u>
Distance	<u>116 links</u>	<u>166 links</u>

Original Bearing Trees Found

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Subsequent Corner Restoration

Year surveyed 1904 By T.M. Fowble  
Location filed: Lake Winnebigoishish Reservoir  
Monument:  
Indicates known corner

Evidence of Subsequent Corner Restoration

Year of search 7/1913 By J.W. Curo, LS 1428  
Location filed: Survey Record #237, Book A, page 607 and 608  
Monument: Set 2.5"x 4' iron pipe, capped with anchor rod  
Found tall stub of NW GLO tree plainly marked and burned  
stump of NE GLO tree, set corner by flat measurement from  
face of witnesses.

Bearing Trees, Reference Objects

Species	_____	_____
Diameter	_____	_____
Bearing	_____	_____
Distance	_____	_____

Bearing Trees, Reference Objects

Species	<u>Jack Pine</u>	<u>Norway Pine</u>
Diameter	<u>8"</u>	<u>6"</u>
Bearing	<u>N 52° E</u>	<u>N 55° W</u>
Distance	<u>71.10'</u>	<u>53.72'</u>

Subsequent Corner Restoration

Year surveyed 2/1914 By J.W. Curo, LS 1428  
Location filed: Survey Record #302, Book B, page 313  
Monument: Found Iron set previously by Curo

Evidence of Subsequent Corner Restoration Found

Year of search \_\_\_\_\_ By \_\_\_\_\_  
Location filed: \_\_\_\_\_  
Monument: \_\_\_\_\_

8/1930, H.D. Craig, U.S. Surveyor, GLO  
Minnesota Historical Society, T144N R31W notes page 12  
Found 2" Cass County galvanized iron pipe, up 4" with 4"  
square pine stake along side and witnesses as follows.  
10" Nor. Pine stump, N 54° E, 116 links 76.56'(GLO) burned  
20" Nor. Pine stump, N 4°30' E, 166 links 109.56'(GLO) burnt  
10" Nor. Pine, N 56°45' W, 82links(54.12')

1/1934, J.A. Gjelhaug, Eng. CCC  
USFS Form 874-9  
Found 2.5" Iron capped pipe, up 1' and marked witness.  
7" N. Pine, N 59° W, 81 1/2 links(53.79') possible 1930 witness

